

The new standard in HDMI matrix technology

The Just Add Power 2G+ Enhanced PoE Receiver has all of the features of 2G models, with these hardware additions:

- **Stereo output with audio delay**
- **CEC Control**
- **USB 2.0 over IP**
- **Null Modem-integrated RS232**
- **Locking HDMI cable**

Mix-and-match! The 2G+ Enhanced PoE Receiver features are fully compatible with all 2G and 2G+AVP models. Enhance an installation by adding 2G+ pieces wherever additional features are needed.



USB 2.0

Compliance	HDCP & RoHS/FCC/CE
Operating Temp	0-60 °C / 32-140 °F
Supported Resolutions	Up to 1080p50/60 Hz PC: 1920 x 1200
Dimensions & Weight	186 x 30 x 127 mm 7.3" x 1.2" x 5.0" 0.45 kg / 1.0 lb
Ports	HDMI Out Ethernet connector 3.5mm Stereo Out 3.5mm RS232 w/ null modem USB 2.0 (x2)
Bandwidth	Up to 150 Mbps
Power Supply (not included)	DC5V, 2A minimum 5.5mm/2.1mm, Positive tip
PoE	10 watts maximum

Features	
Compatible with all 2G products	
CEC control	
Locking HDMI cable	
RS232 with integrated null modem	
Stereo audio output + 170ms audio delay	
USB 2.0 over IP	
All 2G features	
• Stereo or multi-channel audio	
• Instant-seamless Switching	
• Video Wall	
• 2-way RS232 control	
• Image Pull	
• Image Push	
• On-Screen Display	



RS232
STEREO
HDMI OUT
ETHERNET

All measurements in millimeters (mm)

