

The new standard in HDMI matrix technology

The Just Add Power 2G PoE Transmitter is the source-side encoding device in the HD over IP matrix system.

- **Connects to source via HDMI**
- **Connects to network via Ethernet**
- **Instant-seamless Switching**
- **Video Wall**
- **Image Pull**
- **2-way RS232 control**

Not your ordinary matrix! Don't settle for simple matrix control when you can have all of these features built-in. 2G PoE Transmitters are fully compatible with all 2G+ and 2G+AVP models.



Features

Stereo or multi-channel audio
Instant-seamless Switching
Video Wall
Image Pull
2-way RS232 control
Image Push
On-Screen Display

Compliance	HDCP & RoHS/FCC/CE
Operating Temp	0-60 °C / 32-140 °F
Supported Resolutions	Up to 1080p50/60 Hz PC: 1920 x 1200
Dimensions & Weight	187 x 30 x 127 mm 7.4" x 1.2" x 5.0" 0.45 kg / 1.0 lb
Ports	HDMI In Ethernet connector RS232 (Female DB9)
Bandwidth	Up to 150 Mbps
Power Supply (not included)	DC5V, 2A minimum 5.5mm/2.1mm, Positive tip
PoE	10 watts maximum



ETHERNET

HDMI IN

RS232

All measurements in millimeters (mm)

