

## The new standard in SDI matrix technology

The Just Add Power 2G+ SDI Transmitter adds SDI support to the HD over IP system and has all of the features of 2G+:

- **SD-/HD-/3G-SDI formats**
- **Stereo output with audio delay**
- **Local HDMI Loopout**
- **Null Modem-integrated RS232**
- **HDMI Pass-through**



**Mix-and-match!** The 2G+ SDI Transmitter is fully compatible with all 2G and 2G+AVP models and viewable on any Just Add Power Receiver. Add an SDI source to your HD over IP system without the need for an SDI-HDMI converter.



Features	
Compatible with all 2G products	
Locking HDMI cable	
HDMI Pass-through	
RS232 with integrated null modem	
Stereo audio output + 170ms audio delay	
All 2G features	
• Stereo or multi-channel audio	
• Instant-seamless Switching	
• Video Wall	
• Image Pull	
• 2-way RS232 control	

<b>Compliance</b>	HDCP & RoHS/FCC/CE
<b>Operating Temp</b>	0-60 °C / 32-140 °F
<b>Supported Resolutions</b>	Up to 1080p50/60 Hz PC: 1920 x 1200 SDI: SD/HD/3G
<b>Dimensions &amp; Weight</b>	160 x 31 x 127 mm 6.3" x 1.2" x 5.0" 0.4 kg / 0.8 lb
<b>Ports</b>	SDI In HDMI Out Ethernet connector 3.5mm Stereo Out 3.5mm RS232 w/ null modem
<b>Bandwidth</b>	Up to 150 Mbps
<b>Power Supply (included)</b>	DC5V, 2A minimum 5.5mm/2.1mm, Positive tip
<b>PoE</b>	N/A



- ETHERNET**
- SDI IN**
- HDMI OUT**
- STEREO**
- RS232**

All measurements are in millimeters (mm)

